# News Release

**Pro Audio Group**
EV • Telex • Midas • Klark Teknik
Dynacord • RTS • University Sound

## EV (ELECTRO-VOICE©) INTRODUCES QRx212H/75 LOUDSPEAKER AT WINTER NAMM

*QRx212H/75 Two-Way, High-Power Full-Range System for Active or Passive Operation and Horizontal Mounting*

**ANAHEIM, CA (January 16th, 2003):** EV (Electro-Voice®) is introducing the dual 12-inch two-way full-range QRx212H/75 loudspeaker, the newest addition to its already successful line of QRx loudspeakers, at this year's Winter NAMM, Booth #6778. QRx loudspeaker systems provide high-quality audio solutions for both portable and demanding installations.

QRx loudspeakers function as a main PA and as stage monitors. For low-profile/limited clearance installations, QRx requires less space than standard trap boxes when used in horizontal box hangs, and arraying is simplified.

The **QRx-212H/75** is a full-range, two-way loudspeaker system that incorporates two 12-inch woofers and a 3-inch voice coil compression driver on an asymmetrical 75-degree x 50-degree rotatable constant directivity horn. In factory delivered position, the horn provides a 15-degree up/35-degree down vertical coverage pattern. The rotatable horn allows 180-degree rotated mounting possible, while keeping nominal coverage. The fully rotatable horn means pattern control is user-determined, regardless of cabinet position. The QRx-212H/75 also offers excellent horizontal mounting and boundary surface coupling.

The QRx-212H/75 features 43 – 18,000 Hz (-10 dB) frequency response (measured on axis) and 650 watts continuous power handling (passive). The QRx-212/75 features two DL12Sx 12-inch woofers, the new large-format DH-7 driver with a 3-inch voice coil on fully rotatable asymmetrical CD horn, Ring Mode Decoupling (RMD™), two Neutrik® Speakon® connectors, and 13-ply Birch plywood. The QRx-212H/75 also features an integrated crossover with an acoustic crossover frequency of 2,000 Hz. To ensure proper performance in a variety of conditions and by operators of varied experience, the QRx-212H/75 also features dynamic protection circuit for independent protection of both ways against thermal overload.

For more information, call 1-800-392-3497, or visit www.electrovoice.com.

*(more)*

**Telex Communications, Inc.**
12000 Portland Avenue, Burnsville, MN 55337 • Phone: 952.884.4051 • Fax: 952.346.4985

# News Release



Electro-Voice® is a professional audio brand of Telex Communications, Inc., a leader in the design, manufacture and marketing of sophisticated audio, wireless, multimedia, broadcast and communications equipment for commercial, professional and industrial customers. Telex Communications markets its products in more than 80 countries under the brands EV®, Telex®, RTS™, AudioCom™, RadioCom™, Dynacord®, Midas®, Klark Teknik®, University Sound® and others.

For more information, call 1-800-667-3968, or visit www.electrovoice.com

**James Edlund**
**Public Relations Manager**
**Telex Communications, Inc.**
**12000 Portland Ave. South**
**Burnsville, MN 55337**
**Phone: 952-736-3901**
**Fax: 952-736-4582**
**E-mail: James.Edlund@telex.com**