



# Electro-Voice

## Preliminary



# ZX1-Sub

## **ZX1-Sub - 12" Subwoofer**

- **Passive 12" subwoofer delivering outstanding performance**
- **Ideally suited to both mobile applications and fixed installation**
- **Tailored to use with ZX1, EVID and EVU compact loudspeaker systems**

A range of features make the ZX1-Sub a standout choice in its class. Its EV-engineered 12" EVS-12S woofer operates in the 42 Hz to 200 Hz (-10 dB) frequency range and boasts a frequency response of 53 Hz – 125 Hz (-3 dB). The nominal impedance of the subwoofer is 8 ohms and its maximum sound pressure level is 127 dB. A robust, 15-mm-thick internally braced wooden enclosure with two side handles, a structured coating and a sturdy steel grille

ensure both reliable performance and rugged durability in day-to-day use. The ZX1-Sub's two recessed NL4 type connectors (2) are wired in parallel, permitting the input signal to be looped through and making it possible to operate full-range loudspeakers such as the ZX1 together with the ZX1-Sub using a single amplifier channel. With its compact dimensions (40 x 44 x 46 cm), the latest member of the ZX series weighs-in a just under 20 kilos.



# ZX1-Sub



## Specifications

Model No.	F01U267692
Response: (-3dB)	53Hz – 125 Hz
Freq. Range: (-10dB)	42 Hz – 200Hz
Rec. Hipass Frequency:	38 Hz
Axial Sensitivity:	94 dB
Max. Measured SPL:	127 dB
Coverage:	Omnidirectional
Power Handling:	400W Cont.; 800W Prog.; 1600W Peak
LF Transducer	EVS-12S, 305 mm (12") Woofer
Nominal Impedance	8 $\Omega$
Connectors	NL4 Type Connector (2)
Enclosure Material:	9-ply 15 mm Plywood, internally braced, with textured paint
Grille:	16 GA steel with black powdercoat
Dimensions	400mm x 444.5mm x 457.2 mm (15.75 in x 17.50 in x 18.00 in)
Net Weight	19.8 Kg (43.6lb)
Shipping Weight:	25.4 kg (56.0 lb)