

EV SxA360

**THE SUPERCHARGED VERSION OF THE
WORLD'S MOST POPULAR LOUDSPEAKER**



- **Compact Size**
- **Lightweight (16,6 kg / 36 lbs)**
- **350 W LF + 150 W HF Output Power**
- **High Sensitivity, 129 dB Maximum SPL**
- **2" Voice Coil DH2T Compression Driver**
- **Dynamic Filters provide Overload Protection & Linear Response**

- IN A PACKAGE THAT'S LIGHT AS A FEATHER!



Telex Communications Inc. 12000 Portland Ave South, Burnsville, MN 55337, USA • Phone: 1-800-392-3497, Fax: 1-800-955-6831
 © 2004 Telex Communications, Inc. • SUBJECT TO CHANGE WITHOUT PRIOR NOTICE • PA20647 • Internet: www.electrovoice.com

The Electro-Voice® SxA360 sets a new standard for powered speakers. Its design provides the user a simple to use system with plenty of power in a very compact package.

This is a full range loudspeaker ideal for most applications requiring high-quality sound. Whether as a front-of-house system as side fill, delay line or stage monitor, the SxA360 offers a unique combination of high SPL, natural frequency response, and dynamic headroom in an extremely lightweight package. Its linear response provides excellent feedback-free sound without additional equalization. Built-in suspension points and pole mount make it easy to position for your application without expensive accessories. The high-frequency section of the SxA360 utilizes a molded in, 65° x 65° constant-directivity horn driven by the by the DH2T 2" voice coil, wide-bandwidth compression driver. This unique pattern contributes to high intelligibility, vocals sound natural yet "cut through" in reverberant, noisy rooms. The Sxa360 features a positive locking AC connector and is shipped with a 5 m (15 ft.) AC power cord and a set of S200 monitor feet. In combination with the SbA760 powered 15" subwoofer the SxA360 can be expanded to an exceptional 3-way active PA system.



SPECS

Freq. Response (-10 dB)	60 Hz - 18 kHz
Horizontal Coverage	65°
Vertical Coverage	65°
LF Amplifier Power	350 W RMS
HF Amplifier Power	150 W RMS -
Max SPL (calculated)	129 dB
LF Transducer	12" (300 mm) DL12BFH Woofer
HF Transducer	1.0" (25 mm) exit DH2T Comp. Driver

Connectors:

Line Inputs	XLR and 1/4" phone Combination
Balanced Output	XLR
Power Requirement	110-130 VAC, 50-60 Hz, or 220-240 VAC, 50-60 Hz 600 Watts
Enclosure Material	Copolymer
Grille	Powder Coated Steel
Dimensions (H x W x D) :	586 x 429 x 312 mm (23.1" x 16.9" x 12.3")
Net Weight	16,6 kg (36 lbs)
Shipping Weight	18,4 kg (40 lbs)