

SPECIFICATIONS

MODEL	FREQUENCY RESPONSE***	POWER HANDLING (Secondary load at 8 ohms)	(SECONDARY POWER TAPS AND REFLECTED IMPEDANCES)				INSERTION LOSS (Max.)	LINE VOLTAGE (Primary)	MOUNTING HOLE CENTERS	OVERALL DIMENSIONS	WEIGHT
			Tap Setting	Imp. for 25V Line**	Imp. for 70W Line**	Wire Color*					
5015	50 Hz to 10 kHz	15W	0.5W	1.3K	10K	Yellow	1 dB	70.7V or 25V	2"	1.15/16" (4.92cm) H x 2-3/8" (6.03cm) W x 1-7/8" (4.76cm) D	1.5 lbs. (0.68 kg)
			1.0W	680	5K	Brown					
			1.9W	340	2.6K	Orange					
			3.8W	170	1.3K	Green					
			7.5W	84	670	Blue					
5030	100 Hz to 10 kHz	30W	15W	42	335	Purple	1 dB	70.7V or 25V	2-13/16"	1-15/16" (4.92cm) H x 2-7/8" (7.30cm) W x 2" (5.08cm) D	2 lbs. (0.91 kg)
			1.25W	500	4K	Yellow					
			2.5W	250	2K	Brown					
			5W	125	1K	Orange					
			10W	63	500	Green					
5060	50 Hz to 7 kHz	60W	15W	42	333	Green	1 dB	70.7V or 25V	3-1/8"	2-5/16" (7.46cm) H x 3-11/16" (9.37cm) W x 2-1/4" (5.72cm) D	2.5 lbs. (1.14 kg.)
			30W	21	167	Blue					
			60W	10	83	Purple					
			1.88W	332	2.7K	Yellow					
			3.75W	167	1.3K	Brown					

*** ± 3 dB

** $\pm 10\%$

*Gray (Common)